Teamac®
Marine & Industrial Coatings

TECHNICAL DATA SHEET

TDS: TMV60714

THINNERS 14

600/V607/14

DESCRIPTION:

Thinners 14 is a Hydrocarbon solvent.

RECOMMENDED USE:

Teamac Thinners 14 is used to thin and clean down products such as Marine Gloss, Metalastic and Metalcote. See specified thinners for paint being used.

AVAILABILITY:

1 litre, 2.5 litre

FINISH:

N/A

COLOUR:

Clear thin liquid.

TYPICAL S.G. (SPECIFIC GRAVITY):

0.76 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

N/A

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

40 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application restrictions N/A

Method: N/A

Thinner (Max vol): N/A

Nozzle size: N/A

Nozzle pressure: N/A

Cleaning solvent: N/A

Recoat interval: N/A

SURFACE PREPARATION:

N/A

For further advice contact Teamac Technical Services on +44(0)1482 320194

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

TEAMAC
Lockwood Street, Hull HU2 0HN
Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: info@teamac.co.uk
www.teamac.co.uk

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

N/A

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

N/A

REMARKS:

Flamability limits in air:- Lower - 1% by volume
Upper - 6% by volume

Vapour pressure:- 0.8mm HG @ 20°c

HEALTH AND SAFETY:

See safety data sheet - SDS 10695

ISSUED:

16 December 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specificaton. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 320194.

TEAMAC
Lockwood Street, Hull HU2 0HN
Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266
Email: info@teamac.co.uk
www.teamac.co.uk