Gelcoat Cleaner/Stain Remover

Boatcare

Suitable for Cleaning of GRP & Painted Surfaces

PRODUCT DESCRIPTION

A high strength penetrating gel that quickly and easily removes stains, such as light rusting and yellowing, on GRP and painted surfaces.
* Reactive formula - no need to scrub surfaces, avoids scratching.
* Thick gel consistency - will not run when applied to vertical surfaces.

PRODUCT INFORMATION

Colour	YMA622
Specific Gravity	1.02
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

	Drying							
	Overcoating Substrate Temperature							
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	To avoid scratches caused by dirt, clean the surface with Super Cleaner and rinse with water before treatment.
Method	Apply Gelcoat Cleaner/Stain Remover generously with a brush, sponge or cloth using circular movements. Leave for 5 to 10 minutes, then rinse with fresh water.
Hints	**Mixing** Stir or shake thoroughly.
Some Important Points	Protect from frost. Product temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/40°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/40°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on GRP and painted surfaces.
Number of Coats	1
Recommended DFT	
Application Methods	Brush /Cloth/Sponge.

TRANSPORTATION,STORAGE AND SAFETY INFORMATION

Storage

GENERAL INFORMATION:
Exposure to air and extremes of temperature should be avoided. For the full shelf life of Gelcoat Cleaner/Stain Remover to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight.

TRANSPORTATION:
Gelcoat Cleaner/Stain Remover should be kept in securely closed containers during transport and storage.

Safety

GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.
DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.
Remainders of Gelcoat Cleaner/Stain Remover cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

X and International are registered trademarks of Akzo Nobel.

Regional Addresses

Head Office
International Paint Ltd
P O Box 20980
Oriel House
16 Connaught Place
London W2 2ZB
United Kingdom
tel: +44 (0) 171 479 6000
fax: +44 (0) 171 479 6500

European Region
International Paint Ltd
Stoneygate Lane
Felling, Gateshead
Tyne & Wear NE10 0JY
United Kingdom
tel: +44 (0) 191 469 6111
fax: +44 (0) 191 438 3977

Asia Region
International Paint Singapore (Pte) Ltd
449 Tagore Industrial Avenue
01-03 Hong Joo Industrial Building
Singapore 787820
tel: +65 6453 1981
fax: +65 6453 1778

Australasia Region
International Paint
115 Hyde Road
Yeronga, Brisbane
Queensland 4104
Australia
tel: +61 (0) 7 3892 8866
fax: +61 (0) 7 3892 4287

North America Region
International Paint Inc
2270 Morris Avenue
Union
New Jersey 07083
USA
tel: +1 (0) 908 686 1300
fax: +1 (0) 908 686 8545

South America Region
International Paint
Rod Rap tavares, KM 18.5
Predio Administrativo 11
Butanta CEP 05577-300
Sao Paulo, Brazil
tel: +55 (0) 11 3789 2000
fax: +55 (0) 11 3789 2200

Ref: 05000142
Issue Date: 4-Sep-2004
Supersedes: 6-May-2004